



Barrier Free Architecturals  
 480 E Franklin Rd, #108, Meridian, ID 83646  
 1(877) 717-7027 or visit: www.barrierfree.org  
 EMAIL: info@barrierfree.org

## Specifications

# Shower Curtain Standard - White

## ACXCURTXXXX Series Shower Curtain, White

- Material: Vintex SoffTICK Linen 50099-10.5
  - Vintex Safe Guard® Certified
  - phthalate free
  - environmentally friendly, no heavy metals as per Safe Guard® certification
  - elegant linen surface finish
  - permanent fluid barrier
  - flame retardant for the life of the fabric
  - hypo-allergenic, non-irritating
  - combats bacterial & fungal growth
  - durable polyester base fabric
  - light weight
- Color: White
- Porcelain weights sewn into the bottom hem
- Stainless steel grommets that are spaced every 6" across the top of the curtain



Measurements	Model No.
42" x 74"	KACXCURT0001
48" x 74"	KACXCURT0002
54" x 74"	KACXCURT0003
62" x 74"	KACXCURT0004
66" x 74"	KACXCURT0005
80" x 74"	KACXCURT0006
116" x 74"	KACXCURT0007
100" x 60"	KACXCURT0008
42" x 76"	KACXCURT1002
66" x 36"	KACXCURT1076
102" x 73"	KACXCURT1086
42" x 86"	KACXCURT1095
78" x 48"	KACXCURT3010
66" x 66"	KACXCURT3023

### Typical Physical Properties

Property:	Typical Test Results:	Test Method:
Configuration:	85.9 % vinyl 14.1 % polyester	ASTM D751
Total Weight (oz/yd <sup>2</sup> ):	10.5	ASTM D3776
Tear (lb):	37 (w) x 23 (f)	ASTM D751
Tensile (lb/inch):	120 (w) x 97 (f)	ASTM D751
Adhesion (lb/inch):	15 (w) x 25 (f)	ASTM D751
Antimicrobial:	100% contact inhibition 100% surface inhibition	AATCC 147-2004 AATCC 30-2004
Fire Retardancy:	Pass Pass	NFPA 701 2010 TM2 Cal. Tech. Bull. 117 Sec E

