



Barrier Free Architecturals  
480 E Franklin Rd, #108, Meridian, ID 83646  
1(877) 717-7027 or visit: [www.barrierfree.org](http://www.barrierfree.org)  
EMAIL: [info@barrierfree.org](mailto:info@barrierfree.org)

## Specification

# Grab Bar Stainless Steel Straight

Tubing material: Type 304 (18-8) stainless steel

Tubing size: 1-1/4" O.D. x .049" (18 ga.) wall thickness

Tubing size: 1-1/2" O.D. x .049" (18 ga.) wall thickness

### Flange style:

Mounting flanges are constructed of Type 304 (18-8) stainless steel, heliarc welded to the bar to form a single structural unit.

Concealed, 14 ga. x 3" dia.

### Finish:

Standard - satin stainless

Optional Powder coating (P.C.) in various colors

Epoxy type DuPont #ELW-505-S9

Adhesion per ASTM D3359 Method B

Accelerated aging per ASTM G26 Method A

Gloss per ASTM D 523

Flexibility per ASTM D 522 Method A

### Meets:

-ADA Guidelines section 4.26

-ASTM F 466-85 (re-approved 1990): Standard Consumer Safety Specification for Grab Bars and Accessories installed in the Bathing Area

-Federal Specification WW-P 541-8b, amendment 1 4-16-1990

-ANSI 117.1 1998: Buildings and Facilities providing Accessibility and Usability

-F.H.A., V.A. and HUD requirements

-Commonwealth of Massachusetts Architectural Access Board

-California Building Code

-City of Los Angeles

### Installation:

Factory Installed with #10x1-1/4" stainless TEK screws in integral plywood backing.

