

Adult Phenolic Folding Shower Seats

"L" shape (RH/LH)

Configuration:
60/61 Series
Phenolic

Application Use:

Architectural

Commercial

Institutional

Residential

Specifications

Folding shower seat manufactured by ELCOMA from 1" (25mm) diameter, 18 gauge and 1.25" x 1.25" (32mm x 32mm), 16 gauge, type 304 stainless steel tubing with #4 satin finish. Wall mount brackets shall be 12 gauge type 304 stainless steel. Solid Phenolic seat shall be 1/2" (13mm) thick and shall be fire and mildew resistant. Shower Seat shall comply with all applicable federal, provincial and local building and safety codes.

Woodgrain shown, Also available in White

**** LEFT HAND SHOWN , RIGHT HAND OPPOSITE ORIENTATION ****



Custom sizes are available to suit special requirements.

26" x 21" (660mm x 533mm)	White	Model # 61-PH2601
26" x 21" (660mm x 533mm)	Woodgrain	Model # 61-PH2615
28" x 21" (711mm x 533mm)	White	Model # 61-PH2801
28" x 21" (711mm x 533mm)	Woodgrain	Model # 61-PH2815
30" x 21" (762mm x 533mm)	White	Model # 61-PH3001
30" x 21" (762mm x 533mm)	Woodgrain	Model # 61-PH3015
32" x 21" (812mm x 533mm)	White	Model # 61-PH3201
32" x 21" (812mm x 533mm)	Woodgrain	Model # 61-PH3215
34.5" x 21" (876mm x 533mm)	White	Model # 61-PH34501
34.5" x 21" (876mm x 533mm)	Woodgrain	Model # 61-PH34515

Model #60 - (for right hand)

Elcoma Shower Seats have been designed and tested to withstand 400lbs. (182kgs) of load when properly installed.* This exceeds HUD, FHA, VA, ADA, ANSI and other federal, provincial, and local codes.

*Shower seats can only be as strong as what they are mounted to.

It is imperative when installing any shower seat to consult with a qualified contractor to insure you have sufficient backing.

